

# BRUTALE

## 920cc

### ENGINE

Type	Four cylinder, 4 stroke, 16 valve
Timing system	"D.O.H.C", radial valve
Total displacement	921 cm <sup>3</sup> (56.2 cu. in.)
Compression ratio	13:1
Starting	Electric
Bore x stroke	73,0 mm x 55,0 mm (2.87 in. x 2.17 in.)
Max. horse power - r.p.m. (at the crankshaft)**	96 kW (129 HP) at 10500 r.p.m.
Max. torque - r.p.m.	95 Nm (9.7 kgm) at 8100 r.p.m.
Cooling system	Cooling with separated liquid and oil radiators
Engine management system	Magneti Marelli 5SM ignition - injection integrated system with Mikuni throttle body; induction discharge electronic ignition; sequential timed "Multipoint" electronic injection
Clutch	Wet, multi-disc
Transmission	Cassette style; six speed, constant mesh
Primary drive	50/79
Gear ratio	
First gear: Speed*	13/38 109.7 km/h (68.1 mph) at 11600 r.p.m.
Second gear: Speed*	16/34 150.8 km/h (93.6 mph) at 11600 r.p.m.
Third gear: Speed*	18/32 180.3 km/h (111.9 mph) at 11600 r.p.m.
Fourth gear: Speed*	20/30 213.7 km/h (132.7 mph) at 11600 r.p.m.
Fifth gear: Speed*	22/29 243.2 km/h (151.0 mph) at 11600 r.p.m.
Sixth gear: Speed*	19/23 265.0 km/h (164.5 mph) at 11600 r.p.m.
Final drive ratio	15/40

### ELECTRICAL EQUIPMENT

Voltage	12 V
Alternator	350 W at 5000 r.p.m.
Battery	12 V - 8.6 Ah

### DIMENSIONS AND WEIGHT

Wheelbase	1430 mm (56.30 in.)
Overall length	2045 mm (80.51 in.)
Overall width	775 mm (30.51 in.)
Saddle height	825 mm (32.48 in.)
Min. ground clearance	140 mm (5.51 in.)
Trail	103,5 mm (4.07 in.)
Dry weight	183 kg (403.5 lbs)
Fuel tank capacity	23 l (6.07 U.S. gal.)

### PERFORMANCE

Maximum speed*	265.0 km/h (164.5 mph)
----------------	------------------------

### FRAME

Type	ALS Steel tubular trellis
Rear swing arm pivot plates: material	Aluminium alloy

### FRONT SUSPENSION

Type	Type Marzocchi "UPSIDE - DOWN" telescopic hydraulic fork with external and separated adjustment of rebound and compression damping and of spring preload
Rod dia.	50 mm (1.97 in.)
Travel on leg axis	125 mm (4.92 in.)

### REAR SUSPENSION

Type	Progressive, Sachs single shock absorber with rebound damping and spring preload adjustment
Single sided swing arm: material	Aluminium alloy
Wheel travel	120 mm (4.72 in.)

### BRAKES

Front brake	Double floating disc with Ø 310 mm (Ø 12.2 in.) diameter, with steel braking disc and steel flange
Front brake caliper	Brembo Radial with 4 pistons Ø 32 mm (Ø 1.26 in.)
Rear brake	Single steel disc with Ø 210 mm (Ø 8.27 in.) diameter
Rear brake caliper	Nissin with 4 pistons - Ø 25.4 mm (Ø 1.00 in.)

### WHEELS

Front: Material/size	Aluminium alloy 3.50 " x 17 "
Rear: Material/size	Aluminium alloy 6.00 " x 17 "

### TYRES

Front	120/70 - ZR 17 M/C (58 W)
Rear	180/55 - ZR 17 M/C (73 W)

### FAIRING

Material	Thermoplastic
----------	---------------

### RETAIL PRICE

Price VAT included	<b>€ 11.990</b>
--------------------	-----------------



MATT TITANIUM

MATT PEARL WHITE

MATT BLACK

\* Top speed attained on closed course.

\*\* Limited power versions available on demand.

Every country could have a price variation due to local import duties and taxes.